

2025 Meetinghouse Standard Light Fixture Schedule																					
Type	Description	Lamp	Lamp Temp	Rep 1 Manufacturer 1	Quantity Model 1	Rep 2 Manufacturer 2	Model 2	IRC Manufacturer 3	Build26 Model 3	Rep 4 Manufacturer 4	Model 4	SCCO Manufacturer 5	Model 5	Layton Manufacturer 6	Model 6	Maxlite Manufacturer 7	Model 7	Sylvania			
F1	1x4' LED PANEL, DAMP LOCATION RATED. SPECIFY WHETHER THE FIXTURE IS TO BE RECESSED, SURFACE OR GROUND MOUNTED.	40W LED 2400 LM	3500 K	Metalux	16CGT5-L3C3	Lithonia	CXP 1X4 5000LM 800CRI 35K 50V MH10 2T MVOLT	Columbia	C8T14-A-L3CS-EDD-FX14	Daybrite	JFP24SL835-4-DS-UNV-DIM	Liron	PLB3-1X4-LW3CCT-40W/FH14	Maxlite	MLFP14V13WCS	Leadvance	62607- PANEL-F38S03UNV/D8C714GWH				
F2	0.14" THICK ACRYLIC LENS. 2x4' SURFACE MOUNTED LOW PROFILE TROFFER WITH STEEL HOUSING. 0-10V DIMMABLE	65W LED 7000 LM	3500 K	Metalux	24GB-LD5-72-A19-156-LN	Viscor	LST-A 2X4 LED 8 35K 077L P97	Columbia	LIT24-35W-SM-F5A12125- EDU	HE Williams	12-4-LR4@35-FAF12125DIM- UNV	1st Source Lighting	RSD-RCSM24-7000L-35K-D92-4- D0	Maxlite	MLFP24G540WCS- ML24G4SMK	Leadvance					
F3	2' WALL MOUNTED VANITY FIXTURE WITH ACRYLIC DIFFUSER. *ELECTRONIC BALLAST SEE SPEC 265100 MOUNT AT CEILING.	26W LED 2600 LM	3500 K	Metalux	28CLED-LD4-20SL-F-UNV	Lithonia	BLWBP 20L ADP G210 LPS35	Columbia	MPS2-35W-MW-CW-EDU- MPSCE	Daybrite	F50230L835-UNV-DIM	Liron	SP2-2FT-LW3CCT-25W	Maxlite	LS3-2U13WCS- CB	Leadvance	64115- WRAP/FLV/S030UNH/D8SC724WH				
F4	4' WALL MOUNTED VANITY FIXTURE WITH ACRYLIC DIFFUSER. *ELECTRONIC BALLAST SEE SPEC 265100. MOUNT ABOVE MIRRORS AT 7'-0". SEE SHEET A408.	45W LED 5000 LM	3500 K	Metalux	48CLED-LD4-20SL-F-UNV	Lithonia	BLWBP 40L ADP G210 LPS35	Columbia	MPS4-35W-MW-CW-EDU- MPSCE	Daybrite	FSW45SL835-UNV-DIM	Liron	SP2-4FT-LW3CCT-45W	Maxlite	LS3-4U23WCS- CB	Leadvance	64116- WRAP/FLV/S050UNH/D8SC748WH				
F5	4' SINGLE LAMP STRIP LIGHT. SURFACE OR CHAIN SUSPENDED. WITH WIRE GUARD.	50W LED 5400 LM	3500 K	Metalux	45LSTP4040DD-UNV-AVC-4	Lithonia	CSS-L48-AL03 MVOLT S3WV3-80CRI/LW/GCSS	Columbia	MPS4-35W-FW-EDU- MPSW4-C-3HC	HE Williams	75R-4-L50/835-WG-75-DIM- UNV	Cree	LS4-60L-835-R-4U-10V	Maxlite	LS3-4U23WCS- CB	Leadvance	65215- STRIP24/044UNV/D835/48/UWH 4'				
F6	AIMABLE LED COVE STAGGERED LIGHT FIXTURE.	10W LED 1100 LM	3500 K	Metalux	25NV-19SL-LW-UNV-L-835	ALW	CVP 2 1 BT IW S2 05 35 80. AN V01 SW UNV	Columbia	MPS2-30W-FW-EDU	Pinnacle Architectural	C-835LO-2'-VC-U-FSD-1-0-N	Cree	FLD-OL-25-D2-07-E-UH-WH-350- DIM 35K								
F7	AIMABLE LED COVE STAGGERED 4' LIGHT FIXTURE.	20W LED 2200 LM	3500 K	Metalux	45NV-33SL-LW-UNV-L-835	ALW	CVP 2 1 BT IW S4 05 35 80. AN V01 SW UNV	Columbia	MPS4-30XW-FW-EDU	Pinnacle Architectural	C-835LO-4'-VC-U-FSD-1-0-N	Cree	FLD-OL-25-D4-07-E-UH-WH-350- DIM 35K								
F8	AIMABLE LED COVE STAGGERED 4' FIXTURE.	28W LED 3080 LM	3500 K	Metalux	45NV-41SL-LW-UNV-L-835	ALW	CVP 2 1 BT IW S4 07 35 80. AN V01 SW UNV	Columbia	MPS4-30W-FW-EDU	Pinnacle Architectural	C-835MO-4'-VC-U-FSD-1-0-N	Cree	FLD-OL-25-D4-14-E-UH-WH-350- DIM 35K								
F9	AIMABLE COVE 8' LONG STAGGERED LED FIXTURE.	72W LED 8000 LM	3500 K	Metalux	8TNSX-90SL-LW-UNV-835	ALW	CVP 2 1 BT IW S8 10 35 80. AN V01 SW UNV	Columbia	MPS8-30W-FW-EDU	Pinnacle Architectural	C-835HO-8'-VC-U-FSD-1-0-N	Cree	FLD-OL-25-D8-14-E-UH-WH-350- DIM 35K								
F10	6" APERTURE RECESSED DOWNLIGHT WITH LED RETROFIT KIT AND SHALLOW HOUSING. WHITE TRIM AND LENSE. 1-1/4' CEILING FLANGE.	13W LED 1000 LM	3500 K	Halo	LT56129FS1EW1R	Maxlite	SSRD-6R13TRCS-W	Portor	RT-DL-S2-B-6L16W-5CCT-277	Current	LXK886130WVVO	Elco	EL617C7RWE1780CA	Maxlite	SSRD-6R13TRCS-W	Leadvance	62873- RT661A/1200ST95C3/BAWH/F26				
F11	8" APERTURE DOWNLIGHT WITH WHITE TRIM. DAMP LOCATION RATED.	27W LED 2000 LM	3500 K	Halo	PR820D010 PR8M12HDM	Maxlite	SSRD-8R23TRCS-W	Liton	CHR28UE-D10-CR8L-225W- T35	Current	LXK989330WHAQ	Elco	F810L2039W2/ELFLU2002	Maxlite	SBRD-8R23TRCS-W	Leadvance	62609-RT62000UNV/D9SC85ATAA 71709-LED/RTB/FRAME				
F12	30" DIAMETER DOUBLE SEALED BOWL FIXTURE WITH MACHINED ALUMINUM TRIM RING. WITH FULLY SEALED DOUBLE BOWL BOTTOM OF FIXTURES ELEV. = 113" 0" 50% Uplight, 50% downlight	(7)13W A21 LED 10,000LM 90 CRI	3500 K	Evergreen	SHP-RBR-P30-136L-9-WF9	Craft Metal	SC3010L DOK 1 D15 TRDPM WA TRDPC	Le Lampiste	BWL-S-D-30/XX/30-LED/74- DBWL-LDS-CLA-SA	Lightway	QL101B-MDNH-10E26-NL- STANDARD. FINISH-STESLN-XXOAH- TOPDOMILENS										
F13	36" DIAMETER DOUBLE SEALED BOWL FIXTURE WITH MACHINED ALUMINUM TRIM RING. *ELECTRONIC BALLAST WITH FULLY SEALED DOUBLE BOWL BOTTOM OF FIXTURES ELEV. = 113" 0" 50% Uplight, 50% downlight	(10)15W A21 LED 14000LM 90CRI	3500 K	Evergreen	SHP-RBR-P36-156L-9-WF9	Craft Metal	SC3612L OPH 1 D15 TRDPM WA TRDPC	Le Lampiste	BWL-S-D-36/XX/36-LED/106- DBWL-LDS-CLA-SA	Lightway	QL102B-MDNH-14E26-NL- STANDARD. FINISH-STESLN-XXOAH- TOPDOMILENS										
F14	WALL SCONCE WITH SEMISPHERICAL ACRYLIC LENS AND ALUMINUM TRIM RING TO MATCH PENDANT FIXTURES. SEE ARCHITECTURAL FOR MOUNTING.	20W 2000 LM	3500 K	Evergreen	VE-WCSM-12-12W-9-WF	Craft Metal	SC180GS OPH 1 D15 WNB WA TRDPC	Le Lampiste	BWL-WS-D-12-7-5-1LED/13- LDS-CLA-SA-DBWL	Stonco	LPW16-30-WW-G3-UNV-SCB4										
F15	SURFACE 4' TRACK, TWO CIRCUIT, WITH 3 AMP CURRENT LIMITER.		3500 K	Halo	L642P1C941CB300	JUNO	TU4FT WH TU1CLF11 WH T1-CB 3A WH	Liton	LPC04-W1 P99-1-C-30-W	Nora	NT-2302W-NT-2348W2-56	Elco	EC004W/EC840W-3A								
F16	SURFACE 8' TRACK, TWO CIRCUIT WITH 5 AMP CURRENT LIMITER		3500 K	Halo	L642P1C941CB300	JUNO	TU8FT WH TU1CLF11 WH T1-CB 3A WH	Liton	LPC08-W2 LP99-1-C-30-W	Nora	NT-2306W-NT-2348W5A	Elco	EC008W/EC840W-5A								
F17	SURFACE CYLINDRICAL SPOT LAMP HOLDER COMPATIBLE WITH TRACK.	1-PAR 38 LED REPLACEMENT 2000 LM DIMMABLE	3500 K	Halo	L81211FL9030P	JUNO	RS30 WH T40F/WH	Liton	LT0831W-TS35-LP913-W	Nora	NTF-860L930M10W	Elco	ET650WW								
F18	PAR38 TRACK LAMP HOLDER. *LAMP COLORS 8-WHITE, 4-RED, 4-BLUE, 4-AMBER.	1-PAR 38 LED REPLACEMENT 2000 LM DIMMABLE	3500 K	Halo	L81211FL9030P	SATCO	SATCO SKU: S22216 WHITE S29480 RED, S28482 BLUE S29483 AMBER	Liton/Sunlite	LT-650W_87935-SU (White), R1475-SU (Red), R1477-SU (Blue), R1479-SU (Amber)	Nora	MTH-128W	Westinghouse	5007100/3314700/3314900/33 43100					Lamp Only 41865- LED14-6P48P30M930TLNFL 25GL			
F19	SURFACE CERAMIC LAMP HOLDER. PROVIDE METAL WIRE GUARD.	1-A19 LED REPLACEMENT 1000 LM	3500 K	Pass & Seymour														Lamp Only 42366- LED11A19DIM9352ZYWRB4			
F20	18' ALUMINUM POLE HINGED PARKING AREA LIGHTING 208 VOLTS. SEE FIXTURE SCHEDULE NOTE. TYPE III DISTRIBUTION. POLE MOUNTED LIGHT FIXTURE. PROVIDE WITH VANDAL RESISTANT HARDWARE.	50W DIMMABLE LED 6000 LM	3000K	Lumark	RRV-PA1A-720-LIT3-SA-SC	Lithonia	RSK1 LED P1 30K R3 MVOLT SFA DDBXD SSAH 18 4C DM18AS DDBXD9	Beacon	BAB1-80L-50-3K7-3-UNV- A30U-SCBA-SSAB18-40A-1- R3-SCBA-VNR	Gardco	DFP-S-P03-800-T3M-AR1-UNV- SCBA	Cree	DSQ-M-C-6L-30K7-3M-LB-B2	Maxlite	M7520M-WCSBFCR-PL-SSHA- 41811-AB-D4 (M SERIES) DB	Leadvance					
F21	WALL MOUNTED. WET LOCATION FINISH TO MATCH PARKING LOT FIXTURES. PROVIDE FIXTURE WITH INTEGRAL BACK BOX. PROVIDE WITH VANDAL RESISTANT HARDWARE.	27W LED 2000 LM	3000K	Lumark	AVCS2A	Lithonia	WXP1 LED P2 30K MVOLT DQD0E	Exo	SG2-20-3K7-ET-UNV-DRT. SCP20E	Stonco	LPW16-30-WW-G3-UNV-SCB4	Cree	DSOW-C-2L-30K7-3M-LA-WML- B2	Maxlite	M7520M-WCSBFCR	Leadvance	61515-				
F22	2x4' RECESSED FIXTURE WITH CENTER ACRYLIC LENS. PROVIDE WITH 1.5" ADJUSTABLE GYP CEILING FLANGE	25W LED 4000 LM	3500 K	Metalux	24CZ2-40-UNV-L835-C01	Lithonia	STAKS 2X4 AL06 S3WV7/ DQ24	Columbia	LCAT24-S-35L042G-EDU- F24	HE Williams	LT-24-L40/835-AF-DIM-UNV	Liron	LED2NTE-2X4DIM- LW35/PL2V4FM	Maxlite	MLV724D2WCS- ML24G4FK	Leadvance	VOLUMES4S/034UNV/D835/24U/WH F2459-FR1A24GWH-24 Fluore Kit 61515-				
F23	2x4' RECESSED FIXTURE WITH CENTER ACRYLIC LENS.	45W LED 5000 LM	3500 K	Metalux	24CZ2-50-UNV-L835-C01	Lithonia	STAKS 2X4 AL06 S3WV7	Columbia	EC24	HE Williams	LT-24-L52/835-AF-DIM-UNV	Liron	LED2NTE-2X4DIM-LW35	Maxlite	MLV724D2WCS- CB	Leadvance	VOLUMES4S/034UNV/D835/24U/WH				
F24	EXIT SIGN. PROVIDE DIRECTIONAL ARROWS AS SHOWN ON PLANS. UNIVERSAL MOUNTING. DOUBLE/SINGLE SIDED. 90 MIN BATTERY	5W LED	3500 K	Sure Lites	6DX78G	Lithonia	EXRG FL MB	Compass	CEG	HE Williams	EXIT-G-EM-WHT-D	Liron	LEDXTRC-R/G	Maxlite	EX-ROW	Leadvance					
F25	8" Wall Washing recessed fixture with aimable optics. 90 CRI or greater. R9-50, 0-10V Dimmable	9W 900 LM	5000K	Halo	RA56L59FSQ2W1VWH	Lithonia	LINWRW-50-10-LRW-6-WB- LSS35VOLT-C-G210			HE Williams	BAR-LD-9-50-DIM-UNV-O-M- OF-C-HWT			Maxlite	RR46109CSW	Leadvance	41946 LED12BL48FGDIM830DC255 LED13ST19DIMCL9SC3TRP-4/C5				
L1	T8 LED Type C replacement lamp. Specify color temperature to match the other lamps in the building	12W 2200 LM	3000K															Leadvance	41946 LED12BL48FGDIM830DC255		
L2	A19, A21 LED replacement lamp. 90 CRI	13W 1100 LM	3000K																Leadvance	1FSU	
L3	A19, B10 Candelabra style LED replacement lamp with white filament	2W 200lm	3000K																	Leadvance	42663 LED2810CDIM827FLWHRP4